



DATA INQUIRY SHEET

6633-872

PARK PAC

Capacity (Actual BTUH)	Cooling - 13,700
Electrical Rating	115 VAC, 60 HZ, 1 Phase
Cooling Full Load AMP's at A.R.I. Standard Condition	Compressor - 10.4 Fan Motor - Outdoor - 1.9 Fan Motor - Indoor - 1.8 Total - 14.1
Running Watts: (Cooling) A.R.I. Standard Condition (80 F. DB/67 F. WB Indoor, 95 F. DB Outdoor)	1540
Running Watts: (Cooling) A.R.I. Maximum Condition (95 F. DB/71 F. WB Indoor 115 F. DB Outdoor)	2050
Compressor Locked Rotor Amps	67
Compressor Ohm Ratings (approx.) C = Common, S = Start, R = Run	(C-S) 1.8 (C-R) .5
Metering Device	Capillary Tube
Refrigerant Charge	24.0 oz.
Evaporator Air Delivery (CFM)	535 CFM - High Speed
Generator Size	See "Generators" Below
Unit Weight (pounds)	116 lbs.
Use time delay fuse or circuit breaker (U.L. H.A.C. R. Type C.S.A.) Rated at 20 amps. Supply wires 12 AWG Min. (Copper)	

ACCESSORIES: 8330A3241 Digital Mercury-Free, Non-Programmable Electronic Thermostat
6633-6151 Duct Collar Package

GENERATORS:

It is not the policy of RV Products to size generators for application in Recreation Vehicles or related structures. However, when sizing generators, the total electrical power consumption in Watts must be determined and taken into consideration, such as:

- A. Maximum running watts of the air conditioner at A.R.I. maximum operating conditions (See Specifications).
- B. Power consumption of electronic ovens, toasters, coffeemakers, television sets, refrigerators, lights, etc.
- C. Generators do lose capacity under the following conditions: (1) Altitude increases above sea level, (2) Temperature increases above certain outdoor design temperatures, and (3) Lack of maintenance.

RV Products
A Division of Airxcel, Inc.
P.O. Box 4020
Wichita, KS 67204

