









Mono Laser Printer

HL-L5000D







Cost efficient



Speed

Ideal choice for business & small offices

The HL-L5000D uses high-yield toner cartridges and offers fast print speeds up to 42 ppm and auto duplex printing to save money, time and paper. It features flexible paper handling, easy connectivity and a backlit LCD display.

- Flexible Local Connectivity
- Comprehensive Application Compatibility
- Flexible Paper Handling
- High-Quality Printing
- Toner Save Mode
- Easy-to-Use Control Panel
- Customer Support

HL-L5000D

Specifications:

Print Technology	Electrophotographic Laser
LCD Display (type/size)	1-line LCD
Paper Size (maximum)	Paper Tray: Up to 8.5" x 14" (legal) Multipurpose Tray: 3.0" - 8.5" (W)/5.0"-14" (L)
Print Speed (maximum) ¹	Up to 42 ppm
Time to First Page⁴	Less than 7.2 seconds
Print Resolution (maximum)	Up to 1200 x 1200 dpi
Processor	800 MHz
Emulations	PCL6, BR-Script3*, IBM Proprinter, Epson FX, PDF version 1.7, XPS Version 1.0
Automatic Duplex	Yes
Paper Input Capacity (maximum)∞	250-sheet capacity paper tray, 50-sheet capacity multipurpose tray
Optional Input Capacity (maximum)* $^{\infty}$	1,340 sheets via optional trays
Output Capacity (maximum) [∞]	150 sheets (face down), 1 sheet (face up)
Media Types	Plain Paper, Letterhead, Coloured Paper, Recycled Paper, Bond, Labels, Envelopes (up to 10)
Media Weights	Standard Paper Tray: 16 to 32 lbs. Multipurpose Tray: 16 to 53 lbs.
Memory (std./max.)	128MB/128MB
Standard Interfaces	Hi-Speed USB 2.0, Parallel
Operating Systems Compatibility	Windows®: XP Home/XP Professional/XP Professional x64 Edition/Windows Vista®/Windows® 7, 8, 8.1, 10/ Windows Server®2003/2003 R2 (32/64 bit)/2008/2008 R2/2012/2012 R2 Mac® OS X® v10.8.5, 10.9.x, 10.10.x Linux
Security Features	Lock Slot, Secure Print
Maximum Monthly Duty Cycle [◊]	Up to 50,000 pages/month
Recommended Monthly Volume	Up to 3,500 pages/month
Warranty	1-year limited warranty

Supplies & Accessories*:

TN-820	Standard Yield Toner Cartridge (approx. 3,000 pages)▼
TN-850	High-Yield Toner Cartridge (approx. 8,000 pages)▼
DR-820	Drum Unit (approx. 30,000 pages)^
LT-5500	Optional 250-Sheet Capacity Paper Tray
LT-6500	Optional 520-Sheet Capacity Paper Tray

Carton Contents:

Brother HL-L5000D	
Standard Yield Toner Cartridge (3,000 pages) [▼]	
DR-820 Drum Unit (30,000 pages) [^]	
Quick Setup Guide	
Installation CD-ROM	
AC Power Cord	

Setup Information:

UPC Code	012502641742
Unit Dimensions	373 x 388 x 255 mm (WxDxH)
Unit Weight	10.5 Kg
Carton Dimensions	485 x 450 x 371.5 mm (WxDxH)
Carton Weight	12.4 Kg



At your side support. Online or live chat - free support for the life of your printer. At Brother, we want to ensure that your experience with us is exceptional. Visit us at brother.ca where you can download the latest product drivers and software, view product manuals, learn how to get the most out of your product with how-to videos and find answers to frequently asked questions.



Working with you for a better environment

At Brother, our green initiative is simple. We strive to take responsibility, act respectfully and try to make a positive difference to help build a society where sustainable development can be achieved. We call this approach Brother Earth. www.brotherearth.com







- Based on one-sided printing. Change from default setting required. From ready mode and standard tray. PostScript®3 TM compatible.

- Additional purchase required.

 Maximum capacity based on using 20 lb. paper.

 Maximum number of printed pages per month can be used to compare designed durability between like Brother products.

 For maximum printer life, it is best to choose a printer with a duty cycle that far exceeds your print requirements.
- The recommended range of monthly printed pages to achieve the best possible performance and printer life. Printers are intended to handle occasional usage beyond this range with little or no effect. Consistently printing above the recommended print volume, however, may adversely affect the print quality or life of the machine. It is always best to choose a printer with an appropriate recommended
- interpretation and the participant of the control o