

PT-P900 & PT-P950NW

PT-P900 Series

Desktop Thermal Transfer &
Laminated Label Printers



only
118mm wide x 192mm high
x 145mm deep

Wireless connectivity
- connect directly to a
Window PC, iOS and Android
Smartphone or Tablet

Produce Premium Quality,
UL certified¹ Laminated Labels
on-demand in strips or individually



PT-P900W

PT-P900W
with battery
(with optional Battery Base charger)

PT-P950NW
with TDU

Brother PT-P900W and PT-P950NW wireless desktop thermal transfer and laminated label printers come as a complete solution that includes printer, label design and print software, future-proof optional accessories, and a full length P-touch tape. These small footprint printers produce wide, premium quality laminated labels at 360dpi print resolution, up to 32mm print height on 36mm tape, and a built-in dual blade automatic cutter that can produce a strip of pre-cut labels.

The PT-P900W and PT-P950NW - complete on-demand labelling solutions for applications that require premier quality labels that stand up in harsh environments. Brother's TZe and HGe tapes provide resistance to chemicals, UV, and abrasion for true industrial applications.




brother
at your side

Specifications

Models	PT-P900W	PT-P950NW
Type of Printer	Powered Desktop Label Printer	Powered Network Label Printer
Print Technology	Laminated Thermal Transfer	
Print Resolution	360x360 dpi (Standard), 360x720 dpi (High Resolution), 360x180 dpi (Draft)	
Print Width	1.26" (32mm)	
Print Speed	Up to 2.3 ips (60mm/sec) at 360x360 dpi, up to 3.1 ips (80mm/sec) at 360x180 dpi	
Cutter	Automatic Dual Blade Cutter (Full and Easy-to-Peel Strip Cutting)	
Media	Brother HGe & TZe Tapes, HSe Heat Shrink Tube	
Media Sizes (width)	36mm, 24mm, 18mm, 12mm, 9mm, 6mm, 3.5mm	
Interfaces	Wi-Fi WLAN 802.11b/g/n, USB 2.0, RS-232C Serial	Ethernet (10/100Base-TX), Wi-Fi WLAN 802.11b/g/n, USB 2.0, Host USB, RS-232C Serial, Bluetooth v2.1 (optional)
LAN IPv4 Protocols	ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), mDNS, WINS, NetBIOS Name Resolution, DNS Resolver, LPR/LPD, Custom Raw Port/Port9100, FTP Server, TFTP Client and Server, ICMP Web Services, LLNMR Responder, SNMPv1/v2c	
LAN IPv6 Protocols	NDP, RA, DNS Resolver, LPR/LPD, mDNS, Custom Raw Port/Port9100, FTP Server, SNMPv1, TFTP Client and Server, ICMP, LLNMR Responder, SNMPv1/v2c	
Wireless Security	SSID (32 Characters), WEP 64/128 bit, WPA2-PSK (AES), LEAP, EAP-FAST, PEAP, EAPTLS, EAP-TTLS	
Operating Systems	Windows Server 2012 R2/2012/2008 R2/2008 (32/64 bit), Windows 10 (32/64 bit) / 8 (32/64 bit) / 7 (32/64bit), Windows Vista (32/64bit), Mac OS X 10.10x – 10.8x, Android 1.6 (or greater), iOS 3.0 (or greater)	
Included Applications	Windows: P-touch Editor v5.1 (with Cable Labelling Wizard), Transfer Manager v2.2, Printer Setting Tool, BRAdmin Lite Mac: P-touch Editor v5.1, Transfer Manager, Printer Setting Tool Android: Mobile Cable Label Tool, Mobile Transfer Express (Available on Google Play Store) iOS: Mobile Cable Label Tool, Mobile Transfer Express (Available on Apple App Store)	
Memory	Download: Up to 99 Templates, Databases & Images (up to 7MB)	
Fonts & Barcodes	Resident Fonts: Helsinki and Letter Gothic Barcode Fonts: Linear: Code39, ITF (I-2/5), UPC-A, UPC-E, EAN8, EAN13, Codabar (NW-7), Code128, GS1-128 (UCC/EAS-128), GS1, DataBar (RSS) 2-Dimensional: PDF417, QR Code, Data Matrix, Maxicode	
Graphics	Compatible Image Formats (BMP, DIB, JPG/JPEG, TIFF, GIF, PNG, WMF, EMF, ICO)	
Power Supply	120-240VAC, 60/50 Hz, 1.8 Amps AC Adapter, Li-ion Rechargeable Battery (optional)	
Carton Contents	PT-P900W or PT-P950NW, 24mm x 8m Extra Strength Adhesive Tape (TZeS251), AC Adapter (AD9100ESA), AC Power Cord, USB Cable	
Unit Dimensions & Weight	118 x 192 x 145mm (WxHxD), 1.5 Kg	
Energy Star Qualified	Yes	
Warranty	1-year Limited Warranty	

Brother tapes come in easy to load, drop in cartridges and a variety of sizes and colours. Advanced Brother thermal transfer printing and laminate technology create durable, versatile labels that last.



Optional Accessories

Battery Base Charger (PA-BB-002)

Bluetooth Module (PA-BI-002)

Barcode Scanner Kit (PA-BR-001)

Li-ion Rechargeable Battery (PA-BT-4000LI)

Touch Panel and Display Unit (PA-TDU-003)

Serial Interface Adapter (PA-SCA-001)

Images are for illustrative purposes only. Actual output (such as font and margins) may vary. All trademarks and registered trademarks referenced herein are the property of their respective companies. All specifications are subject to change without notice.
© 2016 Brother International Corporation (Canada) Ltd. BROTHER and Brother product names and service names are either a trademark or a registered trademark of Brother Industries, Ltd. 10/2016 - 75358

brother
at your side