

RECEIPT & LABEL MOBILE PRINTING SOLUTIONS



**THE RuggedJet™ SERIES IS FAST,
TOUGH AND MEETS THE NEEDS
OF MOBILE PROFESSIONAL
ANYWHERE, ANYTIME.**

**Built tough and efficient for
mobile professionals.**

- Fast print speeds for higher productivity
- Competitive total cost of ownership
- Prints a wide range of receipts and labels from 2 to 4 inches wide.
- Powerful set of drivers and control languages to meet the demands of a variety of vertical market applications
- Super-durable design for tough environments

| TECHNICAL SPECIFICATIONS | | |
|--------------------------|---|---|
| | RJ-4030 | RJ-4040 |
| Printing Technology | Direct Thermal | |
| Print Resolution | 203 dpi | |
| Maximum Printing Speed | 5 ips | |
| Dimensions (W x H x D) | 162 mm x 176 mm x 77 mm (6.38" x 6.93" x 3.03") | |
| Weight with Battery | 850 g. (1.87 lbs.) | |
| User Interface | Three buttons, Four LEDs | |
| Memory | RAM:32MB / Flash:16MB | |
| Print Width – Max | 104 mm (4.09") | |
| Roll Width – Max/Min | 118 mm (4.64") / 51 mm (2.0") | |
| Maximum Roll Diameter | 58 mm (2.28") | |
| Brother Genuine Media | Receipts: Non-coated, Top-coated; Weatherproof / Labels: Top-coated | |
| Sealing Certification | IP54 | |
| Drop Protection | 1.8m (6ft.) (Under Brother™ standard environment) | |
| Barcodes | Linear: CODE 39, Intlv 2 of 5, EAN-8, EAN-13, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions, CODABAR, CODE 128, GS1-128 (UCC/EAN 128), Postnet, GS1 Databar (RSS14, RSS14 Stacked, RSS14 Truncation, RSS14 Stacked Omnidirection), GS1 Databar (RSS Limited), GS1 Databar (RSS Expanded, RSS Expanded Stacked) 2-Dimensional: QR Code (model 1, model 2, micro QR), Maxi code, PDF417 (Standard, Truncate), MicroPDF417, Data Matrix (Square, Rectangular) | |
| OS Support | Drivers: Windows® XP, Windows Vista®, Windows® 7 (RJ-4030/4040); Windows® Server 2003, 2008, 2008R2 (RJ-4040 only) SDKs: Windows® CE 5.0 & higher, Windows® Mobile 5.0 & higher, Android™ 2.2 & higher. PDF printing: SDKs for Windows® Mobile 5.0 & higher, and Android™ 2.2 & higher. | |
| Printer Languages | BPL (P-touch® Template 2.0), ESC/P, Raster | |
| Emulations | ZPL II® | |
| Software/Utilities | P-touch® Editor 5.0, P-touch® Transfer Manager 2.1, BRAdmin Light, BRAdmin Pro, Network setting tool | |
| Interface | USB, Serial (RS-232C), Bluetooth (Ver. 2.0+EDR, Class2) | USB, Serial (RS-232C), Wi-Fi (IEEE 802.11 b/g/n) |
| WLAN Security | No | WEP (64 /128), TKIP, AES, WPA-PSK, WPA2-PSK, EAP-FAST, EAP-LEAP |
| Resident Fonts | 14 BMP & 3 Outline fonts | |
| Battery Life | 500 charge cycles (50% battery capacity assurance) | |
| Charging Time | 6 Hours | |
| Power Options | Rechargeable Li-ion Battery, AC Adapter, DC Vehicle Adapter | |
| Options/Accessories* | Rechargeable Li-ion Battery, Shoulder Strap, Protective Case, Vehicle Mount, 4-Bay Battery Charger, DC Vehicle Adapter, AC Adapter, Serial Cable, Magnetic Card Reader | |
| Warranty | 2-year "bumper-to-bumper" warranty* | |

Ask us about our accessories*

Premium Brother™ Papers for the RuggedJet™ Line

RuggedJet™ models accept a variety of premium Brother™ thermal media

Receipt Paper (4" wide)

- Standard Receipt Paper
- Premium Receipt Paper
- Weatherproof Receipt Paper



Label Rolls (Die-cut media)

- 4" x 1" Labels
- 4" x 2" Labels
- 4" x 3" Labels
- 4" x 4" Labels
- 4" x 6" Labels



*Requires additional purchase. †See limited warranty for details. For warranty information, please visit brother.ca. RuggedJet™ Specifications subject to change without notice. Mac is a trademark of Apple Computer, Inc., registered in the U.S.A and other countries. Microsoft, Windows, the Windows logo and/or other Microsoft products referenced herein are either registered trademarks of Microsoft Corporation in the U.S. and/or other countries. Brother and its logo are trademarks of Brother Industries Ltd., Japan. All specifications are subject to change without notice. All registered trademarks referenced herein are the property of their respective companies. Printed in Canada.