



### Features and Benefits

- ◆ Dries fast
- ◆ High hiding
- ◆ Low spatter
- ◆ Interior use
- ◆ Available in white
- ◆ Easy soap and water clean up
- ◆ Flat sheen hides surface imperfections
- ◆ VOC's are ≤ 100g/L – White

### Recommendations

- ◆ Good for walls or ceilings in:
  - \* Bedrooms
  - \* Living rooms
  - \* Dining rooms

### Limitations

- ◆ Not recommended for trim, woodwork or metal.
- ◆ All wood must be properly sealed to prevent tannin bleed through.
- ◆ Temperature must be 10 °C for a minimum of 48 hours.
- ◆ Do not clean with abrasive cleaners.
- ◆ Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)

### Optimal Performance Guidelines

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. May be sprayed.
- ◆ All surfaces must be clean, dull, dry and free of dust, grease, wax or any other contaminants.
- ◆ Clean surface with T.S.P and rinse
- ◆ While applying paint always maintain a wet edge and a liberal uniform film thickness.
- ◆ Before painting be sure that enough paint is purchased and boxed together to ensure a uniform colour. (especially critical for tints)
- ◆ Rusty nail heads must be sealed with and alkyd.
- ◆ Thinning is not recommended.
- ◆ Always stir thoroughly before and during use
- ◆ Follow label/lid directions for application and primer requirements.

### Technical Information

Gloss Range  
≤ 5 (60 ° angle)  
white untinted

Vehicle Type	Vinyl Acrylic Copolymer
--------------	-------------------------

Spreading Rate  
3.78 liters will cover up to 35 square meters or up to 350 square feet per coat, depending on the porosity and texture of the substrate.

% Solids (based on White)

By Volume: 22.56

By Weight: 38.79

Weight per 3.78L: 5.37 Kg including can

Dry Time

(Based on White under normal conditions)

To Touch: 1 hours

To Recoat: 6 hours

Full Cure: 30 days

Surface Temperature

Minimum: 10 °C or 50 °F

Maximum: 32 °C or 90 °F

Storage Temperature

Minimum: 5 °C or 41 °F

Maximum: 35 °C or 95 °F

Note: 19L plastic pails stored at high temperatures for prolonged periods may experience skinning

Viscosity	86 – 92 Krebs Units
-----------	---------------------

Flash Point	N/A
-------------	-----

Container Sizes

100-00 White	3.7L	1848-954
	18.5L	1848-953

\*Contact your local municipal office for specific disposal guidelines in your region.\*