



Features and Benefits

- ◆ Acrylic/polyurethane Resin
- ◆ Urethane enhanced
- ◆ Excellent adhesion
- ◆ Non-yellowing
- ◆ Resists mildew
- ◆ Available in over 2700 colors
- ◆ Easy soap and water clean up
- ◆ Contains Ceramic Microsphere Technology
- ◆ Stain Guard Technology
- ◆ Self Cross Linking
- ◆ Dirt and stains are easily removed
- ◆ Mar and Scrub resistant
- ◆ May be applied in cooler temperatures
- ◆ MPI - 43
- ◆ Home Owners Lifetime Guarantee
- ◆ VOC's are ≤ 50 g/L- White

Recommendations

- ◆ Good for Interior and Exterior surfaces such as:
*Trim, Door, Cabinetry

Limitations

- ◆ Never apply colour darker than original to vinyl siding.
- ◆ All wood must be properly sealed to prevent tannin bleed through. . 59-20 oil primer or 2 generous coats of 118-00, 24 hours between coats
- ◆ Temperature must be 5 °C for a minimum of 48 hours.
- ◆ Avoid application in extreme heat, direct sun or if rain is imminent.
- ◆ Tinted primer may be required under dark colors.
- ◆ Do not apply in damp conditions or where mildew is present (remove all traces of mildew).
- ◆ May wash with mild detergent after 7 days.

Optimal Performance Guidelines

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. May be sprayed. Note: the best performance will be achieved if this product is used unthinned.
- ◆ Avoid application in humid or cool conditions, which will slow down dry time.
- ◆ Before painting be sure that enough paint is purchased and boxed together to ensure a uniform colour. (Especially critical for tints)
- ◆ All surfaces must be clean, dull, dry and free of dust, grease, wax or any other contaminants.
- ◆ While applying paint, always maintain a wet edge and a liberal uniform film thickness.
- ◆ Follow label/lid directions for application and primer requirements

* Treated with a Fungicide to protect the Paint itself from the growth of mildew

Technical Information

Gloss Range: 28 – 35 (60 ° angle) 00W White untinted		
Vehicle Type	Acrylic/polyurethane Resin	
Spreading Rate Covers 40 to 50 m ² per 4 litres depending on the porosity and texture of the substrate. For best results use product unthinned.		
% Solids (based on White)		
	By Volume:	31.2
	By Weight:	45.46
Weight per 3.64 L: 4.972 Kg including can		
Dry Time (Based on White under normal conditions)		
	To Touch:	2 hour
	To Recoat:	8 hours
	Full Cure:	7 days
Surface Temperature		
	Minimum:	5 °C or 41 °F
	Maximum:	32°C or 90 °F
Storage Temperature		
	Minimum:	5 °C or 41 °F
	Maximum:	35 °C or 90 °F
<i>Note: 19 L plastic pails stored at high temperatures for prolonged periods may experience skinning.</i>		
Viscosity 90-100	Kreb Units	
Flash Point	N/A	
Container Sizes:		
114-00 White	911ml	1858-150
	3.64 L	1858 -600
	18.2L	1858-601
114-04 Medium Base	870ml	1858-160
	3.48 L	1858-610
114-03 Clear Base	850ml	1858-155
	3.40 L	1858-605

NEW HIGH WHITE are designed to be used un-tinted.

This base will not be found in Match-rite colour matching

114-01 – high hide white	911ml	1858-612
	3.64L	1858-611
	18.2L	1858-151

Contact your local municipal office for specific disposal guidelines in your region.