



ACRYL-LOK PRIMER SEALER 118-00

Features and Benefits

- ◆ 100% acrylic
- ◆ Dries fast
- ◆ Interior and Exterior
- ◆ Super adherent
- ◆ Acts as a barrier coat and blocks most stains
- ◆ Easy soap and water clean up
- ◆ Home Owner's Guarantee
- ◆ VOC's are ≤ 200 g/L- White

Recommendations

- ◆ Good for:
 - * Drywall, plaster and masonry
 - * Glossy surfaces, wood, hardboard, ceramic tile and ferrous metal
 - * Act as a barrier for stains; such as smoke damage, crayon, lipstick and most inks

Limitations

- ◆ Some tannin acid may bleed through on woods such as Redwood or Cedar use 59-20.
- ◆ Crayon, ink, greasy and oily surfaces should be solvent wiped with Home Paint Thinner.
- ◆ Never paint in direct sun, extreme heat, or if rain is imminent.
- ◆ Temperature must be 10 °C for a minimum of 48 hours.
- ◆ Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)
- ◆ Must be top-coated.
- ◆ Not recommended for floors or inside showers.

Optimal Performance Guidelines

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. Product can also be sprayed. For best performance use this product is un-thinned.
- ◆ Glossy surfaces and most metals should be DULLED by sanding and solvent wiped.
- ◆ When priming over greasy surfaces or stains such as lipstick or crayon, solvent wash first.
- ◆ While applying paint/primer always maintain a wet edge and a liberal uniform film thickness.
- ◆ **When priming over stains: 2 generous coats of primer are needed to hold back stain from topcoat, allow 24 hrs between coats and before top coating.**
- ◆ Rusty nail heads may require sealing with 64-41.
- ◆ Follow label directions for application.

Technical Information

Gloss Range
 ≤ 10 (60 ° angle)

Vehicle Type Acrylic

Spreading Rate

4 litres covers approximately 40m² per coat, depending on the porosity and texture of the substrate.

% Solids

By Volume: 35.84

By Weight: 52.62

Weight per 3.78 L: 5.24 Kg including can

Dry Time

(Based on normal conditions)

To Touch: 1 hour

To Recoat: 8 hours or overnight

(Priming over stains: 2 generous coats of primer are needed to hold back stain from topcoat, allow 24 hrs. between coats and before top coating.)

Full Cure: 30 days

High humidity and cooler temperatures will slow dry time

Surface Temperature

Minimum: 10 °C or 50 °F

Maximum: 32 °C or 90 °F

Storage Temperature

Minimum: 5 °C or 41 °F

Maximum: 35 °C or 95 °F

Note: 19L plastic pails stored at high temperatures for prolonged periods may experience skinning

Viscosity 86 - 94 Kreb Units

Flash Point N/A

Container Sizes

118-00 - White

946 ml 1850-241

3.78 L 1850-740

18.9 L 1850-786

Contact your local municipal office for specific disposal guidelines in your region.