

Features and Benefits

- Dries fast
- Excellent hiding
- Optimizes top coat's performance
- Low-spattering
- Smooth uniform finish
- Full bodied consistency
- Easy soap and water clean up
- VOC's are $\leq 200 \text{g/L} \text{White}$

Recommendations

- Good for:
- * Drywall
 - * Plaster

* Where drastic colour change is being done

Limitations

- For Interior use only.
- Temperature must be 10 °C for a minimum of 48 hours.
- Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)

Optimal Performance Guidelines

- Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. May also be sprayed.
- All surfaces must be clean, dull, dry and free of dust, grease, wax or any other contaminants
- Clean surface with T.S.P and rinse
- While applying paint always maintain a wet edge and a liberal uniform film thickness.
- Thinning is not recommended.
- Always stir thoroughly before and during use.
- Follow Label/lid directions for application.

Professional Pro 100

Interior Latex Primer 120-00

Technical Information

120-00 White

rechinear miormation	
Gloss Range	
\leq 5 (60 ° angle)	
White untinted	
Vehicle Type	Vinyl Acrylic Copolymer
Spreading Rate	
3.78 liters will cover up to 35 square meters or up to 350 square	
feet per coat, depending on the porosity and texture of the	
substrate.	
% Solids (based on White	
by Volume: 29.4	
by Weight: 49.34	
Weight per 3.78L: 5.25 Kg including can	
Dry Time	
To Touch:	1 hours
To Recoat:	4 hours
Full Cure:	30 days
Surface Temperature	
Minimum: 10 °C	or 50 °F
Maximum: 32 °C	or 90 °F
Storage Temperature	
Minimum: 5 °C	or 41 °F
Maximum: 35 °C	or 95 °F
Note: 19L plastic pails stored at high temperatures for prolonged	
periods may experience skinning	
Viscosity 92 – 9	8 Krebs Units
Flash Point N/A	
Container Sizes	

Contact your local municipal office for specific disposal guidelines in your region.

3.70L

18.5L

1848-956

1848-955