



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® WOOD PRO™ All Purpose Wood Filler

PRODUCT DESCRIPTION

DAP® WOOD PRO™ All Purpose Wood Filler is a high quality, latex-based wood filler formulated to create a surface and body that looks and acts like real wood. It can be used to repair cracks, gouges, holes and other surface defects on furniture, woodwork, moulding, cabinets, panelling, plywood, windows, doors and painted surfaces. This easy-to-use filler is low in odour and cleans up with water. The thick, knife-grade formula can be moulded and sculpted making it ideal for corners, vertical and unsupported surfaces. It offers easy handling by spreading smoothly and evenly. When dry, DAP WOOD PRO All Purpose Wood Filler can be sanded, cut, planed, drilled, nailed or screwed, stained and painted. It is shrink, crack and crumble resistant and provides strong nail and screw anchoring. Interior/exterior use.



PACKAGING	COLOUR	UPC
85 g (3 oz.)	Natural	7079874294
170 g (6 oz.)	Natural	7079874288
170 g (6 oz.)	Golden Oak	7079874291
170 g (6 oz.)	Red Oak	7079874290
170 g (6 oz.)	Walnut	7079874289
170 g (6 oz.)	White	7079874293
453 g (16 oz.)	Natural	7079874283
907 g (32 oz.)	Natural	7079874284

KEY FEATURES & BENEFITS

- Easy-to-use, latex-based formula
- Water clean-up & low odour
- Looks and acts like real wood
- Can be sanded, planed, cut, drilled, screwed & nailed
- Shrink, crack & crumble resistant
- Thick, knife-grade formula can be moulded & sculpted – ideal for corners and vertical surfaces
- Easy handling – spreads smoothly and evenly



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Stainable & paintable
- Strong nail & screw anchoring
- Interior/Exterior use

SUGGESTED USES

Ideal for filling nail holes, gouges, cracks, scratches & imperfections on furniture, woodwork, moulding, cabinets, panelling, plywood, windows, doors and painted surfaces.

APPLICATION

1. Surface must be clean, dry and free of dirt, oil and loose material. De-gloss surface if necessary, for best adhesion.
2. Surface, wood filler and air temperature should be above 4°C.
3. If staining, test wood filler with desired stain on scrap wood before filling to ensure desired stain colour. Stain before filling with wood filler, then use stain to develop desired final finish.
4. Stir product with putty knife before application. For squeeze tubes, knead the tube prior to cutting and extruding material.
5. Apply wood filler into area to be filled. Press firmly into place using a putty knife or tool.
6. Avoid overspreading filler on surrounding surfaces. Overfill slightly to allow for sanding and settling. Most repairs require just one fill. Larger and deeper holes may require more than one application.
7. For larger and deeper holes, apply thin layers to build up thick sections. Allow wood filler to dry before applying next layer.
8. Allow to dry thoroughly before sanding: approximately 3 to 6 hours for shallow fills up to 3mm (1/8") and 36 hours for deeper fills 6mm (1/4") and over. Sand with medium sandpaper.
9. May be painted with latex-based paint immediately after sanding, or after 12 hours if using an oil-based paint.
10. Exterior applications must be coated with latex or oil-based paint or solid colour stain.
11. Reseal container tightly with lid.
12. Keep from freezing.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Stiff Paste
Vehicle	Latex Polymer
Filler	Inert Pigment
Volatile	Water
Solids	78.9% by weight
Odour	Mild
Drying Time	Depending on temperature and humidity: 3 to 6 hours in shallow fills up to 3mm (1/8"); up to 36 hours in deep fills 6mm (1/4") and over.
Shelf Life	12 months
Application Temperature	Above 4°C

CLEAN UP & STORAGE

Wipe off excess filler from surface and tools with a damp cloth before material dries. Dried wood filler must be sanded or scraped away. Reseal tightly with lid after each use. Store in a cool, dry place away from extreme heat or cold

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.ca or by calling **888-DAP-TIPS**.

WARRANTY

LIMITED WARRANTY: DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on “Ask the Expert”

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca