



COVERS UP™ CEILING PAINT & PRIMER

DESCRIPTION AND USES

Zinsser® Covers Up™ Ceiling Paint & Primer In One is a low odour stain blocker and ceiling touch-up paint in one can. It sprays vertically for ease of use, seals water stains, and has a flat white finish that matches new acoustic ceiling tiles.

It is suitable for use on new, primed or previously painted ceiling tiles, drywall, cured plaster, wood, aluminum, iron, steel and galvanized metal, PVC, glossy laminates and other interior surfaces.

PERFORMANCE CHARACTERISTICS

- Seals water stains
- Matches most ceiling tiles
- Dries flat white
- Non-yellowing

PRODUCTS

SKU	Container Size
Z03696	454 g Aerosol
393769	369 g Aerosol

PRODUCT APPLICATION

STAIN BLOCKER

One coat will effectively block most water stains, graffiti, nicotine and smoke stains. If a second coat is desired, allow to dry two hours before re-coating.

CEILING PAINT for CEILING TILES

Use to block water, nicotine, or smoke stains on ceiling tiles. Dries flat and matches the colour of most ceiling tiles.

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper, adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with Krud Kutter® Prepaint Cleaner TSP Substitute or ammonia and water solution or solvent (Do not use TSP). Remove any peeling and/or unsound coatings. Remove any poorly adhering existing coatings by sanding and/or scraping with Gator®. Sand any remaining paint film edges smooth with the surface. Remove interior mould or mildew with Krud Kutter® Mould & Mildew cleaner or with a solution of one cup household bleach per 3.78 L (gallon) of water. Countersink exposed nail heads, spot prime and fill all nail holes and gouges with Zinsser MH Ready Patch® spackling compound, and sand smooth. Wire brush rusty areas.

PRODUCT APPLICATION

SURFACE PREPARATION (cont.)

APPLICATION

Apply at room temperature at 21-27°C (70-80°F) in a well ventilated area. Avoid high humidity. Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Shake often during use. Hold can in an upright position and press finger against the side of the nozzle to activate the spray. Spray 20-30 cm (10-12") from the surface with short 'dusting' strokes, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. **Do not use near open flame.**

DRY AND RECOAT TIMES

Dry and recoat times are based on 21°C (70°F) and 50% relative humidity. Lower temperature and higher humidity will prolong the dry time of the product. Dries to the touch in 30 minutes. Allow a minimum of 2 hours dry time before recoating or applying a topcoat.

CLEAN-UP

Aerosol - Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor. If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

DISPOSAL

Do not burn or puncture the can, even when empty. To dispose of empty containers and unused product, contact your local environmental regulatory agency.

REGULATORY

FUMES MAY CATCH FIRE. CONTAINER MAY EXPLODE IF HEATED. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not smoke. Do not puncture. Do not burn. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Wear rubber gloves and safety glasses. Store away from heat. Keep out of reach of children. FIRST AID TREATMENT: Contains acetone, naphtha, propane, butane. If swallowed, call a Poison Control Centre or doctor immediately. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

**TECHNICAL DATA****COVERS UP™ CEILING PAINT & PRIMER****PHYSICAL PROPERTIES**

		COVERS UP CEILING PAINT & PRIMER
Resin Type		Solvent-based Acrylic
Pigment Type		Titanium Dioxide, Limestone
Solvents		Acetone, Aliphatic Hydrocarbons
MIR		0.80
Fill Weight		454g (13 oz)
Recommended Dry Film Thickness (DFT) per Coat		1.5-2.5 mils (37.5-62.5µ)
Practical Coverage at Recommended DFT (assume 15% material loss)		1.1-1.4 m ² /can (12-15 sq.ft./can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	30 minutes
	Recoat	2 hours
Shelf Life		5 years
Smoke Contribution (ASTM-84-97A)		N/A
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.