



CONSTRUCTION ADHESIVE

4000[®] SUBFLOOR

Exceptional Bond Strength in the Most Extreme Conditions.



**EASY TO GUN
IN COLD TEMPS**

Adhesive won't freeze, easier to gun in the cold



**BONDS WET, FROZEN
& TREATED LUMBER**

Excellent adhesion in extreme weather conditions



**HIGH STRENGTH
WEATHERPROOF BOND**

Prevents floor squeaks & improves structural performance of subfloor assembly



Exterior / Interior
CONSTRUCTION ADHESIVE



CONSTRUCTION ADHESIVE

4000[®] SUBFLOOR

BONDS WET, FROZEN & TREATED LUMBER



CONSTRUCTION ADHESIVE
4000 SUBFLOOR



LIQUID NAILS[®]

Shear Strength to Dry Lumber (psi)*	406	155
Shear Strength to Wet Lumber (psi)*	222	187
Shear Strength to Frozen Lumber (psi)*	248	149

*Pounds per square inch of force required to break bond of adhesive on wet, frozen or treated lumber

FEATURES

- Bonds to Wet & Frozen Lumber
- Prevents Floor Squeaks
- Permanent Bond
- Will Not Freeze

PRODUCT DETAILS

RECOMMENDED USE

Subfloor, wood-to-wood assemblies, glued floor systems & deck installation.

ADHERES TO

- Plywood
- Enhanced OSB
- Concrete
- OSB
- Masonry
- Treated Lumber

APPLICATION TEMPERATURE

-18°C - 49°C (0°F - 120°F)

NOT RECOMMENDED FOR

Most plastics, foamboard, mirror installation, constant water exposure, bonding two non-porous materials, or applications other than subfloor & deck installation.

TYPICAL PHYSICAL PROPERTIES

Solids: 61% - 65% by weight
Shelf Life: 18 months
Skin Time: 15 minutes
Cure Time: 7-14 days

Coverage:
 305 mL
 1/4" bead yields 32 linear ft.
 3/8" bead yields 14 linear ft.
 828 mL
 1/4" bead yields 86 linear ft.
 3/8" bead yields 38 linear ft.

SERVICE TEMPERATURE

-29°C - 60°C (-20°F - 140°F)

SPECIFICATIONS

ASTM D3498 Meets or Exceeds
 AFG-01 Meets or Exceeds
 PFS Certified Tested in accordance with

SKU SPECIFICATIONS

Product Name	Size	Package Code	GTIN	Case Pack	Case Weight	Case Dims. (LxWxH)	Case Volume	Cases Per Pallet
Construction Adhesive 4000 Subfloor	305 mL	0 70798 74881 1	100 70798 74881 8	12	4.8 kg 10.59 lbs.	203 x 152 x 305 mm 8" x 6" x 12"	9.3 L 0.33 cu.ft.	108
Construction Adhesive 4000 Subfloor	828 mL	0 70798 74882 8	100 70798 74882 5	12	12.5 kg 27.65 lbs.	267 x 203 x 432 mm 10.5" x 8" x 17"	23.5 L 0.83 cu. ft.	60

Liquid Nails[®] The Registered Trademark of PPG Architectural Finishes, Inc.