

7200

SUPERIOR

Wall Base Adhesive

1. PRODUCT NAME

ROBERTS® 7200 Wall Base Adhesive

2. MANUFACTURER

Roberts Company Canada, Ltd.
34 Hansen Road South
Brampton, ON L6W 3H4
(866) 435-8665 / (905) 791-4444

3. DESCRIPTION

ROBERTS® 7200 is a superior performing wall base adhesive with quick grab and rapid set-up for the fast installation of wall base.




Features and Benefits

- Excellent holding power and great wet suction
- Strong initial grab for holding heavy rubber wall base
- Fast set-up and non-staining formula
- Easy application and cleanup
- Enviro-Friendly – solvent-free and LEED® compliant; VOC < 1 g/L
- CRI Green Label Plus® Certified – GLP #71129
- GoldGuard® antimicrobial product protection

Uses

For adhering vinyl, rubber and carpet wall base.

Coverage and Trowel Options*

	1/8" x 1/8" x 1/8" Flooring: Wall Base (100mm / 4") Coverage: 14-17 lineal meters per 887 mL / 45-55 lineal feet per 30 oz
	3/16" x 5/32" Flooring: Wall Base (100mm / 4") Coverage: 8.5-10.5 lineal meters per 887 mL / 28-35 lineal feet per 30 oz
	Snozzle Flooring: Wall base (100mm / 4") Coverage: 15-18 lineal meters per 887 mL / 50-60 lineal feet per 30 oz

*The trowel notches referenced are those typically recommended for the type of flooring being installed and are shown as a guide. Consult flooring manufacturer for their specific trowel recommendations.

Substrates

Porous wall surfaces such as gypsum drywall, plaster, brick, concrete block and wood.

Limitations

- ROBERTS® 7200 is not recommended over non-porous or painted surfaces.
- Ensure adequate ventilation during flooring installation.
- Refer to Safety Data Sheet, www.robertsconsolidated.com, industry standards, and manufacturer's guidelines and specific recommendations prior to installation for additional information.

4. TECHNICAL DATA

Product Type:	Acrylic Polymer
Colour:	Creamy tan
Odour:	Mild; odourless when dry
Open Time:	Up to 10 minutes
Working Time:	Up to 30 minutes
VOC:	< 1 g/L
Shelf Life:	1 year in unopened container
Storage:	Freeze-thaw stable to -7°C/20°F, for five cycles Protect from temperatures below -7°C/20°F



5. INSTRUCTIONS

Preparation

Subfloors must be structurally sound, dry, smooth, flat ($\leq 3/16"$ within 10'), level and free of excess moisture/alkali and all substances (oil, wax, grease, paint, oil based sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring or its installation.

All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Expansion or other moving joints must not be filled or covered with flooring. Patching compounds must be suitable for the use application, cement based and polymer-modified, and applied according to the manufacturer's instructions.

Installation

Materials and area temperature must be between 18-35°C/65-95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours afterward. Wrapped or rolled base should lay flat for 24 hours prior to application. Large temperature or humidity increases or decreases can affect the wall base and performance of the installation. Ensure 100% coverage of adhesive to the wall base and the wall surface.

Trim any vinyl wall coverings to 1/4" below the top of the wall base with ROBERTS 10-215 or 10-920-6 knife. Load adhesive cartridge in a cartridge gun. Apply adhesive uniformly to the wall or to the back of the wall base. Press the wall base firmly in place while the adhesive is still wet (typically within 10 minutes). The amount of time in which you have to place the wall base will vary with temperature and humidity.

Use ROBERTS 10-960 Hand Roller to press and smooth wall base into the adhesive. Always roll back to the starting point to prevent stretching the adhesive.

Curing

High temperature and low humidity will cause the adhesive to cure faster.

After installation, restrict foot traffic and moving of heavy objects for 24-48 hours to allow adhesive to cure properly. Premature traffic can cause installation failure.

Clean-up

Fresh adhesive – warm, soapy water.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR DIRECTLY ONTO FLOORING.

6. AVAILABILITY

Packaging

946 mL / 1 U.S. quart Plastic Pail	7200RB001	075378720102
325 mL / 11 U.S. ounce Tube	7200RB313	075378720065
887 mL / 30 U.S. ounce Tube	7200RB852	075378720072

7. WARRANTY

10-Year Direct Bond

ROBERTS warrants that this product will be free from manufacturing defects for 12 months from the date of manufacture, when applied in accordance with ROBERTS' instructions and industry standards. ROBERTS' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.** Any implied warranties arising by operation of law are limited to one year. ROBERTS will not be liable for any incidental or consequential damages.

Visit www.robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9



ROBERTS®, GoldGuard®, and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. CRI Green Label +Plus® is a registered trademark of The Carpet and Rug Institute • LEED®, and its related logo, is a trademark owned by the U.S. Green Building Council® and is used with permission.

11179