



HVAC SILICONE

Professional 100% RTV Silicone Sealant



**EXTREME
TEMP
FORMULA**

**SERVICE
TEMPERATURE
-40°C TO 246°C**

- Superior Adhesion & Durability
- 100% Waterproof / Weather Resistant
- Safe For Incidental Food Contact – NSF Certified
- Multi-Material
- Will Not Crack or Shrink
- Interior / Exterior



HVAC SILICONE



HVAC SILICONE



SERVICE TEMPERATURE
-40°C TO 246°C

Superior Performance for Extreme Temp Applications



Vents



Dampers



Duct Work



Suggested Use

- Air Conditioners
- Ducts
- Furnaces
- Refrigerators
- Dampers
- Aluminum Siding
- Flanged Pipe Joints
- Vents

Adheres To

- Most Metals
- Ceramics
- Porcelain
- Marble
- Non-Oily Surfaces
- Glass
- Fiberglass
- Plastic
- Painted Surfaces
- Other Construction Materials

Specs


- Colours:** White, Clear, Aluminum
- Net Weight:** 10.3 fl. oz.
- Service Temp:** -40°C to 246°C
- Meets Fed. Spec:** ASTM C920 Class 25, TT-S-00230C Class A, TT-S-001543A Class A, FDA Reg. No. 21 CFR 177, 2600 when fully cured. Safe for incidental food contact – NSF Certified.

EXTREME TEMP PERFORMANCE COMPARISON


	175°C	204°C	232°C	246°C
DAP HVAC SILICONE	✓	✓	✓	PASS ✓
Competitor RD	✓	Loss of Flexibility	Loss of Flexibility	FAIL ✗
Competitor B	✓	✓	FAIL ✗	



WILL NOT CRACK OR SHRINK



Formulated to Sustain Sealant Flexibility & Durability



Cracking & Loss of Flexibility at High Temps Resulting in Sealant Failure

MATERIAL	MATERIAL DESCRIPTION	UPC EACH	CASE CODE	SIZE	COLOUR	Case Pack (In)	Case Net Weight (lb)	Case Length (In)	Case Width (In)	Case Height (In)	Case/Pallet
7079874326	DAP HVAC SILICONE	070798743267	10070798743264	300 ML	ALUMINUM	12	9.17	8.00	6.00	12.00	108
7079874327	DAP HVAC SILICONE	070798743274	10070798743271	300 ML	CLEAR	12	8.72	8.00	6.00	12.00	108
7079874328	DAP HVAC SILICONE	070798743281	10070798743288	300 ML	WHITE	12	8.72	8.00	6.00	12.00	108