

## SCREENEZE<sup>®</sup> NO-SPLINE SCREEN PORCH SYSTEM



Available Colors: Bronze & White  
Available Sizes: 8' & 12'

SCREENEZE<sup>®</sup> can be cut and spliced to fit a custom opening up to 150 sq ft!



### SCREENEZE<sup>®</sup> Works!

- No Spline, No Staples
- Reduce Call Backs
- Span Openings Up To 150 Sq Ft
- 10 Year Limited Warranty
- Self Tightening | No Stretching
- Easy Screen Replacement
- Screws Included
- Install on the Inside, Outside Or Center of Your Porch Post/Rail Design
- Install With Mitered Corners Or Use Plinth Kits For Straight Cuts

### INSTALLATION

- Instructions included in shipping tube
- Visit [www.SCREENEZE.com](http://www.SCREENEZE.com) for more info

### SPECIFICATIONS

- PVC vinyl cap made of window grade virgin vinyl with UV inhibitor
- Aluminum base made of solid aluminum alloy
- Baked on polyester paint
- Color coordinated screws included
- Aluminum base is 3/4" x 3/4"
- PVC cap is 3/8" x 1/2"
- US Patent No. 6,378,267

## SCREENEZE® PRODUCT INFORMATION

### ALUMINUM BASE CHANNEL

- Solid 6061 aluminum alloy
- Temper T5
- Baked on polyester paint
- 3/4" x 3/4", 8' or 12' in length

### PVC VINYL CAP

- Window grade virgin vinyl with UV inhibitor
- 3/8" x 1/2", 8' or 12' in length
- Long Term High Temperature Exposure: Under certain conditions, the cap can be affected by reaching an internal temperature of 160°F. Long term exposure at 160°F can cause the shape to change and become ineffective as intended. This can and has happened on a very limited basis. This has occurred primarily with the black cap in extreme conditions. If you are in an area with high UV, west setting sun and little or no UV filter we caution against an Exterior Corner Mount using the Bronze/Black color. If Bronze/Black is your only option, we strongly recommend an Inside Flush Mount to protect the cap from direct sun.

### SCREWS - BRONZE, WHITE, SAND & CLAY

- High tensile strength carbon steel metal to wood fastener
- #10 thread
- 1 ¼" in length
- #8 size head
- Square drive #2 bit
- Tech/drill design for easy penetration through metal
- High thread for faster drilling
- 1000 hour ACQ approved coating
- Color coordinated with SCREENEZE®