

Techniseal®

For your everyday projects look for


THE ORIGINAL

Now at




NOW with NextGel technology for professional results

- Fast setting
- No haze
- For joints from 1.6 mm to 13 mm (1/16" to 1/2")
- 22,7 kg (50 lb.) bag



Dark Granite



Tan



GET THE BEST SOLUTION FOR YOUR PROJECTS

RG+ Polymeric Sand from Techniseal® is a mix of graded sand and binder which is applied dry, compacted, watered and hardens after drying. It is an economical alternative which ensures perfect jointing of pavers for common installations with low demand. It is ideal for yard projects, residential driveways, patios, sidewalks and pedestrian walkways.

Ready to use, it can be used in new installation as well as in renovation. Unlike conventional sand, it remains perfectly stable and in place. It prevents the growth of weeds and the invasion of insects. It effectively resists erosion caused by water, frost, wind, cleaning, etc.

NECESSARY TOOLS:



3 EASY STEPS:

1 SPREAD THE PRODUCT



2 COMPACT THE PRODUCT



3 WET THE JOINTS



TIPS:

- Refer to the complete Technical Data Sheet at techniseal.com.
- It is imperative to allow the installation to **dry completely** before installing the new jointing product.
- Temperature must be above 0 °C (32 °F) for 48 hours following installation.
- Allow a **minimum of 24 hours** in dry conditions (depending on the overall temperature and humidity).
- A wet foundation or surface will cause the activation of the jointing product before compaction and activation. It may also clog the sides of the pavers and prevent the products from filling the entire joints in depth.
- On textured pavers, use a leaf blower to blow surface water into the joints. This will remove any remaining sand and polymer residue, which will prevent hazing.
- Wait 30 days after installation before cleaning and sealing pavers.
- The use of cleaning devices (high pressure washer, etc.) is restricted during the first 30 days.

COVERAGE: For a 22.7 kg (50 lb) bag : 6 to 11 m² (60 to 120 sq. ft.). For a more precise evaluation of the coverage, please refer to the product calculator at techniseal.com.



Jointing Product	Product code	Colour	Size	Units per pallet
RG+	40105160	Dark Granite	22.7 kg (50 lb) (bag)	56
	40100593	Tan	22.7 kg (50 lb) (bag)	56



Techniseal® Jointing products contribute to LEED credits, based on the use of regional and recycled materials.



(03/25)