

TL-1012RSFH-EWL

4.8 lpf / 1.28 Gpf Elongated Toilet

Includes: Slow-Close Seat, Floor Bolts, and Wax Ring

Specifications:

- White vitreous china
- FLUSH GUARD[®] overflow protection
- 17" Plus Height[™] ADA bowl
- Chrome tank lever
- Siphon jet flush action
- 2" Fully glazed ball pass trapway
- 3" Flush valve
- 12" rough-in
- Extra large footprint covers floor marks
- Works with standard plumbing; no special installation required for overflow feature
- Total package with slow-close plastic seat, wax ring, and floor bolts included
- FLUSH GUARD[®] toilets are specially designed to meet the needs of individuals with physical, cognitive, and sensory impairments, enhancing accessibility, safety, and ease of use
- 100% factory flush tested
- Lined Tank



Notes:

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Overall Dimensions:

16 1/8" (W) x 30 1/4" (D) x 31 7/8" (H)

410mm (W) x 768mm (D) x 810mm (H)


Compliance Certifications:

Meets or exceeds the following specs:

- IAPMO cUPC
- ASME A112.19.2-2018/CSA B45.1-18
- ICC A117.1-2017 & ADA Guidelines
- MaP tested 1000g
- IGC 252-2018 Overflow Standard
- Built Environment - 2020, Cal Green - 2022 and LEED[®] v4.1
- EPA WaterSense Specification for Tank-Type Toilets, Version 1.2, June 2, 2014

FLÜSH GUARD[®]

ANTI-OVERFLOW TOILETS



EXTRA LARGE FOOTPRINT

