



WIDER WINGSPAN

OFFERS MORE TORQUE

Colour

22

20

18

Designed and manufactured in Canada, the new PRO-BLU 933 wire connector was developed with the installer's needs in mind.

With an ergonomic design and a wide range of approved wire combinations, this wire connector is a perfect fit for the majority of residential and commercial applications.

External cap

- Ergonomic wing design makes installation easy and painless, even when installing multiple wire connectors.
- Posi-Grip[™] surface provides superior twisting power, even when hands are greasy or damp.
- Finger-friendly plastic for an even more comfortable grip.
- Rounded edge for safe and comfortable installation.
- Made of durable polypropylene resistant to temperatures up to 105°C (221°F). Exclusive Live Action® variable volume spring expands to accommodate even more wires with less twisting effort compared to other wide range wire connectors.

Inner spring

- Live Action variable volume spring expands to accommodate even more wires with less twisting effort.
- Wide range of wire combinations: #22 to #8 AWG, solid or stranded, no pre-twisting required.

14

12

- The square wire spring construction and funnel design gives a positive pressure conductor grip for solid or stranded wires.
- Approved for circuits up to 600 V and lighting fixtures and signs up to 1000 V.
- For copper conductor only.


16

Min.: 1 #22 + 1 #20 Max.: 3 #10 sol

For packaging options, see page D18

Blue





Model

933



Number of cond.		+ Number of cond.	AWG		Number of cond.	AWG	+ Number of cond.
1	22	1	20	_	1	20	1
1	22	2	20		1	20	2
1	22	3	20	_	1	20	3
1	22	4	20		1	20	4
1	22	5	20		1	20	1
1	22	1	18		1	20	2
1	22	2	18	_	1	20	3
1	22	3	18		1	20	4
1	22	4	18		1	20	1
1	22	5	18		1	20	2
1	22	1	16		1	20	3
1	22	2	16		1	20	4
1	22	3	16		2	20	1
1	22	4	16		2	20	2
1	22	5	16		2	20	3
2	22	1	20		2	20	1
2	22	2	20		2	20	2
2	22	3	20		2	20	3
2	22	4	20		2	20	1
2	22	1	18		2	20	2
2	22	2	18	-	2	16	4
2	22	3	18		2	16	1
2	22	4	18		2	16	1
2	22	1	16		2	16	2
2	22	2	16		2	16	3
2	22	3	16		2	16	1
2	22	4	16		2	16	2
3	22	1	20		2	16	1
3	22	2	20		2	16	-
3	22	3	20		3	16	1
3	22	1	18		3	16	1
3	22	2	18		3	16	1
3	22	3	18		3	16	2
3	22	4	18		3	16	3
3	22	1	16		3	16	1
3	22	2	16		3	16	2
3	22	3	16		3	16	1
3	22	-	-		3	16	2
4	22	1	20		3	16	1
4	22	2	20		3	16	-
4	22	1	18		4	16	1
4	22	2	18	-	4	16	2
4	22	1	16	-	4	16	1
4	22	2	16	-	4	16	1
4	22	-	-	-	4	16	2
5	22 Sol.	-	-	-	4	16	1
6	22 Sol.	-	-	_	4	16	1
				_	•	-	

Number			
of cond.	AWG	of cond.	AWG
	16	-	-
5	16	1	14
5	16	1	10
5	16	-	-
6 1	16 14	1	12
1	14	1	
1	14	2	12
1	14	2	12
1	14	3	12
1	14	4	12
1	14	1	10
1	14	2	10
1	14	1	8 Strd.
1	14		-
2	14	1	12
2	14	1	12
2	14	2	12
2	14	3	12
2	14	1	10
2	14	1	8 Strd.
2	14	-	-
3	14	1	12
3	14	2	12
3	14	1	10
3	14	1	8 Strd.
3	14	-	-
4	14	1	12
4	14	1	10
4	14	-	-
5	14	-	-
1	12	1	10
1	12	2	10
1	12	1	8 Strd.
1	12	-	-
2	12	1	10
2	12	1	8 Strd.
2	12	-	-
3	12	1	10
3	12	-	-
4	12	-	-
1	10	1	8 Strd.
1	10	-	-
2	10	-	-
3	10	-	-

8 Strd.