



2210 / CI2236



CI2238 / CI2240



CI4090



CI5153



CI5154

N° de cat.	Alliage	Grosseur nominale (po)	Gamme de serrage (po)		Applications suggérées		Emballage	
			Min.	Max.	AC90 (BX)	Conduit flexible		
RACCORDS COUDÉS À 90°								
2210M2	Zinc	3/8	0,40	0,63	14/2 - 10/2; 14/3 - 10/3; 14/4 - 12/4	3/8	Coquille de 2 unités	
2210-V2-MFP							Flip-Pak de 30 unités	
2210-V2-RP							Sac de 1 unité	
2211M1		1/2	0,65	0,97	8/2; 8/3; 10/4	1/2	Coquille de 1 unité	
2211-V2-RP							Sac de 1 unité	
2214M1		3/4	0,77	1,12	1/0/1 - 4/0/1; 6/2 - 4/2; 8/3 - 3/3; 8/4 - 6/4	3/4	Coquille de 1 unité	
BC2214-V2								
CI2216		Aluminium	1	1,06	1,40	4/0/1 - 350/1; 2/2; 4/3 - 2/3; 6/4 - 4/4	1	
CI2218			1-1/4	1,34	1,65	500/1 - 750/1; 1/3 - 3/0/3; 1/4 - 1/0/4	1-14	
CI2234			1-1/2	1,70	2,15	600/1 - 1000/1; 2/0/3; 1/4 - 3/0/4	1-1/2	
CI2236	2		1,51	2,47	600/1 - 1000/1; 2/0/3 - 400/3; 1/4 - 4/0/4	1-1/2 - 2		
CI2238	2-1/2		2,50	3,08	600/3 - 750/3	2-1/2		
CI2240	3		2,95	3,55	1000/3	3		
CI4090	Zinc		4	4,17	4,62		4	

N° de cat.	Alliage	Grosseur nominale (po)		Gamme de serrage (po)	
		TEM	FLEX	Min.	Max.
COUPLEURS TEM / FLEX					
CI5153	Zinc	1/2	3/8	0,17	0,63
CI5154			1/2	0,75	0,95