



*Professional* **Pro 300**  
**Interior/Exterior Latex Block Filler**  
**392-20**

### Features and Benefits

- ◆ Dries fast
- ◆ Helps smooth and fill porous surfaces
- ◆ Interior and Exterior use
- ◆ White
- ◆ Easy soap and water clean up
- ◆ VOC's are  $\leq 50$  g/L- White

---

### Recommendations

- ◆ Good for:
  - \* Vertical cement
  - \* Cinder or masonry block
  - \* Crazed plywood

---

### Limitations

- ◆ Not recommended for spray application.
- ◆ All wood must be properly sealed to prevent tannin bleed through.
- ◆ Temperature must be 10 °C for a minimum of 48 hours.
- ◆ Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)
- ◆ Must be top-coated with 7 days.

---

### Optimal Performance Guidelines

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended.
- ◆ Do not thin.
- ◆ May be applied with window squeegee to fill crevices.
- ◆ While applying paint, always maintain a wet edge and a liberal uniform film thickness.
- ◆ All surfaces must be clean, dull, dry and free of dust, grease, wax or any other contaminants.
- ◆ Always stir thoroughly before and during use.
- ◆ Follow label directions for application.

### Technical Information

Gloss Range  
< 10 (60° angle)

---

Vehicle Type Vinyl Acrylic Copolymer

---

#### Spreading Rate

4 litres will cover up to 10 - 14 square meters or up to 100-200 square feet per coat, depending on the porosity and texture of the block or substrate.

---

#### % Solids (based on White)

by Volume: 38.48

by Weight: 56.17

Weight per 3.78 L: 5.70 Kg including can

---

#### Dry Time

To Touch: 1-2 hours

To Recoat: 8 hours

---

#### Surface Temperature

Minimum: 10 °C or 50 °F

Maximum: 32 °C or 90 °F

---

#### Storage Temperature

Minimum: 5 °C or 41 °F

Maximum: 35 °C or 95 °F

Note: 19L plastic pails stored at high temperatures for prolonged periods may experience skinning

---

Viscosity 106 – 110 Kres Units

---

Flash Point N/A

---

#### Container Sizes

392-20 – White 18.5 L 1828-437