



Features and Benefits

- ◆ An excellent quality interior wall paint
- ◆ A tough 100 % Acrylic formulation
- ◆ Excellent washability and stain removal
- ◆ Low spatter
- ◆ Dries fast, 2 hour re-coat
- ◆ Low sheen helps hide surface imperfections
- ◆ Soft Touch finish
- ◆ Available in over 2700 colours
- ◆ Paint/Primer in one
- ◆ Easy soap and water clean up
- ◆ Home Owner's Guarantee

Specialty Application / Environments

- ☑ Virtually no odor
- ☑ VOC's less than 5 g/L - White
- ☑ Beauti-Tone uses No VOC colourants
- ☑ Meets or exceeds CRGI standards to carry the Green Wise Certification mark
- ☑ Ideal for health care and institutional facilities

Recommendations

- ◆ Good for plaster, drywall ceilings and walls in areas such as:
 - Dining Rooms
 - Living Rooms
 - Bedrooms
 - Nurseries

Limitations

- ◆ Do not allow product the freeze.
- ◆ Colour Tints – may add an odor
- ◆ All wood must be properly sealed to prevent tannin bleed through.
- ◆ Temperature must be 10 °C for a minimum of 48 hours.
- ◆ Stucco or textured ceilings can become soft and damaged by use of a latex product directly applied to it. Seal surfaces with Alkyd Primer/Sealer 59-20 first or top-coat with 50-10.
- ◆ Colour rub off may occur with dark colours.
- ◆ Tinted primer may be required under dark colours.
- ◆ Not recommended for Bathrooms
- ◆ Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)
- ◆ May wash with mild detergent after 30 days.

Optimal Performance Guidelines

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. May be sprayed.
- ◆ While applying paint always maintain a wet edge and a liberal uniform film thickness.
- ◆ Before painting be sure that enough paint is purchased and boxed together to ensure a uniform colour (especially critical for tints)
- ◆ All surfaces must be clean, dull, dry and free of **dust, grease, wax or any other contaminants**. Follow label/lid directions for application and primer requirements

Technical Information

Gloss Range
< 4 (60 ° angle) , < 5 (85 ° angle)
Based on 00W white untinted

Vehicle Type	Acrylic
--------------	---------

Spreading Rate
4 litre will cover up to 40 square meters or up to 400 square feet per coat, depending on the porosity and texture of the substrate.

% Solids (based on White, bases and colours will vary)

By Volume: 39.86

By Weight: 56.95

Weight per 3.64 L: 5.027 Kg including can

Dry Time

(Based on White under normal conditions)

To Touch: 1 hour

To Recoat: 2 hours

Full Cure 30 days

Note: Additional dry time may be required for darker colours, high humidity, or cooler temperatures

Surface Temperature

Minimum: 10 °C or 50 °F

Maximum: 32 °C or 90 °F

Storage Temperature

Minimum: 5 °C or 41 °F

Maximum: 35 °C or 95 °F

Note: 19L plastic pails stored at high temperatures for prolonged periods may experience skinning

Viscosity 98 – 105 Kreb Units

Flash Point N/A

Container Sizes

505-00W – White	911 ml	1852-500
	3.64 L	1852-501

505-03 –Clear Base	3.40 L	1852-503
--------------------	--------	----------

505-04 –Medium Base	3.48 L	1852-505
---------------------	--------	----------

* As calculated by the General Formula outline in the VOC Concentration Limits for Architectural Coatings Regulations.

Contact your local municipal office for specific disposal guidelines in your region.