



Features and Benefits

- ◆ An excellent quality interior wall paint
- ◆ A tough scrubable 100% Acrylic formulation
- ◆ Low spatter
- ◆ Dries fast , 2 hour re-coat
- ◆ Home Owner’s Guarantee
- ◆ Easy soap and water clean up
- ◆ Available in over 2700 colours
- ◆ Low Semi sheen helps hide surface imperfections

Specialty Application / Environments

- ☑ Virtually no odor
- ☑ VOC’s less than 5 g/L - White*
- ☑ Beauti-Tone uses No Voc Colourants
- ☑ Meets or exceeds CRGI standards to carry the Green Wise Certification mark
- ☑ Ideal for health care & institutional applications
- ☑ Meets MPI 43
- ☑ Meets MPI Green Performance Standard (GPS-1 & GPS-2)
- ☑ Meets LEED(excluding LEED for schools)

Recommendations

- ◆ Good for plaster, drywall ceilings and walls in areas such as:
 - Dining Rooms * Living Rooms
 - Bedrooms * Nurseries * Bathrooms

Limitations

- ◆ **Do not allow product to freeze.**
- ◆ Colour tints – may add an odor
- ◆ All wood must be properly sealed to prevent tannin bleed through.
- ◆ Temperature must be 10 °C for a minimum of 48 hours.
- ◆ Stucco or textured ceilings can become soft and damaged with use of latex products directly applied on them Seal surfaces with an Alkyd Primer/Sealer 59-70, or top-coat with 50-10.
- ◆ Colour rub off may occur with dark colours.
- ◆ Tinted primer may be required under dark colours.
- ◆ Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)
- ◆ May wash with mild detergent after 30 days.
- ◆ As calculated by the General Formula outline in the VOC Concentration Limits for Architectural Coatings Regulations.

Formula outline in the VOC

Optimal Performance Guidelines

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. May be sprayed.
- ◆ While applying paint always maintain a wet edge and a liberal uniform film thickness.
- ◆ To ensure uniform colour, be sure to purchase enough paint to box together, before painting
- ◆ All surfaces must be clean, dull, dry and free of dust, grease, wax or any other contaminants.
- ◆ Follow label/lid directions for application and primer requirements

Technical Information

Gloss Range
25 - 35 (60 ° angle)
Based on 00W white untinted

Vehicle Type	Acrylic
<hr/>	
Spreading Rate	4 litres will cover up to 40 square meters or up to 400 square feet per coat, depending on the porosity and texture of the substrate.
% Solids (based on White, bases and colours will vary)	
By Volume:	35.96
By Weight:	48.98
Weight per 3.64 L:	4.954 Kg including can

Dry Time
(Based on White under normal conditions)

To Touch:	1 hour
To Recoat:	2 hours
Full Cure	30 days

Note: Additional dry time may be required for darker colours, high humidity, or cooler temperatures

Surface Temperature

Minimum:	10 °C	or	50 °F
Maximum:	32 °C	or	90 °F

Storage Temperature

Minimum:	5 °C	or	41 °F
Maximum:	35 °C	or	95 °F

Note: 19L plastic pails stored at high temperatures for prolonged periods may experience skinning

Viscosity	98 - 106 Kreb Units
Flash Point	N/A

Container Sizes

525-00W – White	911 ml	1852-608
	3.64 L	1852-607
	18.2L	1852-615
525-03 – Clear	850ml	1852-610
	3.40L	1852-609
525-04 – Medium	870ml	1852-612
	3.48L	1852-611

Contact your local municipal office for specific disposal guidelines in your region.