



**Features and Benefits**

- ◆ Dries fast
- ◆ Resists mildew\*
- ◆ Excellent adhesion even in moist areas
- ◆ 100% Acrylic
- ◆ Durable & Scrubable Finish
- ◆ Washable
- ◆ Available in over 2700 colors
- ◆ Mildew resistant
- ◆ Easy soap and water clean up
- ◆ Home Owner's Guarantee
- ◆ VOC's are ≤ 150 g/L- White
- ◆ Spatter resistant

**Recommendations**

- ◆ Good for:
  - \* Woodwork
  - \* Kitchens
  - \* Bathrooms
  - \* Mud rooms

**Limitations**

- ◆ Not recommended for bare wood.
- ◆ All wood must be properly sealed to prevent tannin bleed through.
- ◆ Temperature must be 10 °C for a minimum of 48 hours.
- ◆ Tinted primer may be recommended under dark colours
- ◆ Do not apply in damp conditions or where mildew is present. (remove all traces of mildew)
- ◆ May wash with mild detergent after 30 days.

**Optimal Performance Guidelines**

- ◆ Always use premium applicators. Synthetic bristle brush and high quality lint free rollers are recommended. May be sprayed.
- ◆ While applying paint, always maintain a wet edge and a liberal uniform film thickness.
- ◆ Before painting, make sure that enough paint is purchased and boxed together to ensure a uniform colour. (especially critical for tints)
- ◆ All surfaces must be clean, dull, dry, and free of dust, grease, wax, or any other contaminants.
- ◆ Follow label/lid directions for application and primer requirements.

\*Treated with a Fungicide to protect the Paint itself from the growth of mildew

**Technical Information**

Gloss Range  
 45-55 (60 ° angle) based on White

---

Vehicle Type      Acrylic

---

Spreading Rate  
 1 litre will cover up to 10 square meters or up to 100 square feet per coat, depending on the porosity and texture of the substrate.

---

% Solids (based on White, bases and colours will vary)  
 By Volume:      35.18  
 By Weight:      47.65  
 Weight per 3.64 L: 4.897 Kg including can

---

Dry Time  
 (Based on White under normal conditions)

|            |           |
|------------|-----------|
| To Touch:  | 1-2 hours |
| To Recoat: | 4-6 hours |
| Full Cure: | 30 days   |

---

Surface Temperature

|          |       |    |       |
|----------|-------|----|-------|
| Minimum: | 10 °C | or | 50 °F |
| Maximum: | 32 °C | or | 90 °F |

---

Storage Temperature

|          |       |    |       |
|----------|-------|----|-------|
| Minimum: | 5 °C  | or | 41 °F |
| Maximum: | 35 °C | or | 95 °F |

Note: 19L plastic pails stored at high temperatures for prolonged periods may experience skinning

---

Viscosity 88 - 96 Krebs Units -based on White

---

Flash Point      N/A

---

Container Sizes

|                     |        |          |
|---------------------|--------|----------|
| 72-00W –White       | 911 ml | 1853-426 |
|                     | 3.64 L | 1853-621 |
|                     |        |          |
| 72-03 – Clear Base  | 850 ml | 1853-417 |
|                     | 3.40 L | 1853-612 |
|                     |        |          |
| 72-04 – Medium Base | 870 ml | 1853-453 |
|                     | 3.48 L | 1853-658 |

**NEW HIGH WHITE are designed to be used un-tinted.**  
 This base will not be found in Match-rite colour matching system.

|                        |       |          |
|------------------------|-------|----------|
| 72-01- High Hide White | 911ml | 1853-454 |
|                        | 3.64L | 1853-455 |

\*Contact your local municipal office for specific disposal guidelines in your region.\*