



# Designer Series

## Interior Acrylic Cabinet & Furniture

### 752-series

#### Features

- ◆ Self-priming on non-porous and over most previously painted surfaces
- ◆ Superior Scrub ability
- ◆ Stain and Mildew resistant
- ◆ Excellent Block resistance
- ◆ Advanced self Cross-linking technology
- ◆ Fast dry and cure time
- ◆ Water clean up
- ◆ Available in over 2700 colors
- ◆ Home Owners Lifetime Guarantee
- ◆ VOC's are ≤ 100g/L

#### Recommendations

- ◆ Good for
  - \* Cabinets, furniture
  - \* Shelving and trim

#### Limitations

- ◆ All wood must be properly sealed w/ 2 coats of 59-20 or 118-00 to prevent tannin bleed through.
- ◆ **Allow 24 hours between coats of primer before top coating.**
- ◆ Temperature must be 10 °C for a minimum 48 hours.
- ◆ Cross ventilation and adequate air exchange will help reduce dry time and minimize odors.
- ◆ Do not apply in damp conditions (remove all traces of mildew)

#### Optimal Performance Guidelines

- ◆ Always use premium applicators. Pure bristle brush and high quality lint free rollers are recommended. May be sprayed. Note: the best performance will be achieved if this product is used un-thinned.
- ◆ While applying paint always maintain a wet edge and a liberal uniform film thickness.
- ◆ Before painting be sure that enough paint is purchased and boxed together to ensure a uniform colour. (Especially critical for tints)
- ◆ All surfaces must be clean, dull, dry and free of dust, grease, wax or any other contaminants.
- ◆ Follow label directions for application and primer requirements.
- ◆ On previously sealed and non porous surfaces, sand surface sufficiently to allow the Cabinet and furniture to adhere soundly.
- ◆ Best performance is achieved if product is used as, without thinning- self priming on sealed surfaces.
- ◆ Some paint surfaces may require sanding to remove surface treatment of existing coating and allow adhesion.

\* Treated with a Fungicide to protect the Paint itself from the growth of mildew

#### Technical Information

Gloss Range 35- 45 (60 ° angle)  
00W White untinted

---

Vehicle Type      Acrylic

---

#### Spreading Rate

Cover 40 to 50m<sup>2</sup> per 4 litres depending on the porosity and texture of the substrate. Colour chosen will affect hiding. For best results use product un-thinned.

---

% Solids (based on White, bases and colours will vary)

By Volume: 37.17

By Weight: 48.67

Weight per 3.64 L: 5.20 Kg including can

---

Dry Time (*Based on White under normal conditions*)

To Touch:            1-2 hours

To Recoat:          12 hours

***Additional dry time may be required for darker colours, high humidity or cooler temperatures. Full hardness and wash ability properties develop after 10 + days.***

---

#### Surface Temperature

Minimum:    10 °C      or    50 °F

Maximum:    32 °C      or    90 °F

---

#### Storage Temperature

Minimum:    5 °C      or    41 °F

Maximum:    35 °C      or    95 °F

*Note: 19L pails stored at high temperatures for prolonged periods may experience skinning*

---

Viscosity- 91 - 99 Krebs Units

---

Flash Point            N/A ° C

---

#### Container Sizes

752-00W - White	911 ml	1880-432
	3.64 L	1880-434
752-04 - Medium Base	870 ml	1880-435
	3.48 L	1880-436
752-10 – Black	925 ml	1880-439
	3.70 L	1880-440
752-20- Espresso	925 ml	1880-441
	3.70L	1880-442

\*Contact your local municipal office for specific disposal guidelines in your region.\*