

Description

Beauti-Tone Interior and Exterior is a premium alkyd spray paint developed to perform optimally through the combination of resin and proprietary formulation. The aerosol offers remarkable adhesion, smooth finish, and excellent coverage for a multitude of surfaces.

Recommended Substrates

Metal – Wood – Fiberglass - Plastic & More

Product Information

A10-10* Black

A10-12* Dark Brown

A10-14* Olive

A10-16* Khaki

**Drastic colour changes, or porous substrate may require a primer coat or more than two coats to achieve a uniform finish.*

Features

Premium Spray Paint

Comfort Spray Tip

Excellent Adhesion

Alkyd Formulation

Fast Drying

Home Owners Guarantee

Benefits

Smooth spray application that promotes exceptional hiding and coverage.

Excellent long-term performance and durable finish.

Regulatory Conformance and Approvals

Not Applicable

Technical Data

Vehicle Type: Alkyd – Clean up with Acetone

Gloss Range: ≤3 (60° angle) based on a A10-10

Spread Rate: Up to 1.3m² or 14 ft² per 340g on smooth and non-porous surfaces. Spread Rate does not include loss due to surface irregularities, surface porosity, material loss, and application method.

Volume Solids*: 8% based on A10-10

Weight Solids*: 16% based on A10-10

**Weight per 340g can – 0.48kg including can and cap*

Drying Time: @ 21°C; 50% Relative Humidity

To Touch – 30 minutes

To Recoat – Within 1 hour or wait 72 hours

To Full Cure – 72+ hours

Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.

Surface Temperature:

Material – 15°C (60°F) to 30° (85°F)

Ambient - 15°C (60°F) to 30° (85°F)

Substrate - 15°C (60°F) to 30° (85°F)

Storage of material at elevated temperatures for prolonged periods may affect product and integrity of packaging.

Viscosity: N/A Krebs Units @ 25°C

Flash Point: Flammable

Disposal: Contact your local environmental regulatory office or your municipality for specific guidelines

Container Sizes:

A10-10 – Black 340 g 1720-098

A10-12 – Dark Brown 340 g 1720-095

A10-14 – Olive 340 g 1720-097

A10-16 – Khaki 340 g 1720-096

General Preparatory Steps and Application Info

-Surface must be clean, dull, and dry.

-Surface must be in sound condition.

-Remove all loose and peeling material, dirt, mildew, grease, stains, and any other surface contamination with appropriate cleaner.

-Sand all glossy (alkyd paints) and rough surfaces.

-Shake well for 1 minute before and during use.

-Hold can upright 8-12" from the surface.

-Spray light coats in a steady back and forth motion while overlapping each pass (this will avoid runs). Do not stop spraying until the piece is coated and repeat. Apply 2-3 light coats a few minutes apart.

-Ideal dry and recoat times are based on 21° @ 50% relative humidity.

-Follow label directives for application and primer requirement. Consult your local Paint Department.

-Cross ventilation and adequate air exchange will help reduce dry time and minimize odours.

-Any solvent soaked tools or rags must be submerged in water to avoid spontaneous combustion. Important to extinguish any pilot light if using in proximity.

Polyethylene (Plastic) / PVC: Certain plastic components may hinder paint adhesion. Apply a test spot first. After 4-5 days, maximum adhesion will be reached.

Clean-up and Storage: Invert and spray to clean nozzle after use. Clean the nozzle tip with acetone.

Application Equipment: N/A

Thinning: N/A