

Description

Beauti-Tone Interior and Exterior is a premium alkyd spray paint developed to perform optimally through the combination of resin and proprietary formulation. The aerosol offers remarkable adhesion, blocks stains and odours, and provides excellent coverage for a multitude of surfaces.

Recommended Substrates

Surfaces with tannin, odours, smoke damage, and household stains.

Product Information

A118-00* – Primer Sealer Block iT

**Some stains may require more than two coats to seal and cover.*

Features

Premium Spray Paint
Comfort Spray Tip
Excellent Adhesion
Alkyd Formulation
Fast Drying
Home Owners Guarantee

Benefits

Smooth spray application and promotes exceptional hiding and coverage.
Excellent sealing qualities.
Will stop most stains and seal persistent odours.

Regulatory Conformance and Approvals

Not Applicable

Technical Data

Vehicle Type: Alkyd – Clean up with Acetone

Gloss Range: ≤10 (60° angle) based on a A118-00

Spread Rate: Up to 1.3m² or 14 ft² per 340g on smooth and non-porous surfaces. Spread Rate does not include loss due to surface irregularities, surface porosity, material loss, and application method.

Volume Solids*: 11% based on A118-00

Weight Solids*: 25% based on A118-00

**Weight per 340g can – 0.465kg including can and cap*

Drying Time: @ 21°C; 50% Relative Humidity

To Touch – 30 minutes

To Recoat – Within 1 hour or wait 72 hours

To Full Cure – 72+ hours

Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.

Surface Temperature:

Material – 15°C (60°F) to 30° (85°F)

Ambient - 15°C (60°F) to 30° (85°F)

Substrate - 15°C (60°F) to 30° (85°F)

Storage of material at elevated temperatures for prolonged periods may affect product and integrity of packaging.

Viscosity: N/A Krebs Units @ 25°C

Flash Point: Flammable

Disposal: Contact your local environmental regulatory office or your municipality for specific guidelines

Container Sizes:

A118-00 –Primer Sealer Block iT 340 g 1850-789

General Preparatory Steps and Application Info

- Surface must be clean, dull, and dry.
- Surface must be in sound condition.
- Remove all loose and peeling paint, dirt, mildew, grease, stains, and any other surface contamination with appropriate cleaner.
- Sand all glossy (alkyd paints) and rough surfaces.
- Shake well for 1 minute before and during use.
- Hold can upright 8-12" from the surface.
- Spray light coats in a steady back and forth motion while overlapping each pass (this will avoid runs). Do not stop spraying until the piece is coated and repeat. Apply 2-3 light coats within a few minutes.
- Ideal dry and recoat times are based on 21° @ 50% relative humidity.
- Follow label directives for application and primer requirement. Consult your local Paint Department.
- Cross ventilation and adequate air exchange will help reduce dry time and minimize odours.
- Any solvent soaked tools or rags must be submerged in water to avoid spontaneous combustion. Important to extinguish any pilot light if using in proximity.**

Persistent odours and stains: Multiple light coats are required to seal most odours and stains.

Clean-up and Storage: Invert and spray to clean nozzle after use. Clean the nozzle tip with acetone.

Application Equipment: N/A

Thinning: N/A