



Fluorescents Aerosol A127-XX

Features and Benefits

- ◆ Interior and exterior
- ◆ Weather resistant
- ◆ Available in 5 colors
- ◆ Quick dry
- ◆ Home Owners Guarantee

Recommendations

- ◆ Good for
 - * Glass, metal, wood and most plastics

Limitations

- ◆ Clean up with Home Paint Thinner.
- ◆ Additional dry time may be required for cool temperatures or high humidity.
- ◆ Do not paint in extreme heat, direct sun or when rain is imminent.
- ◆ Sand surface to insure proper adhesion.
- ◆ All Fluorescent pigments fade in direct sunlight
- ◆ Temperature must be at least 10 °C for a minimum of 48 hours.
- ◆ Cross ventilation and adequate air exchange will help reduce dry time and minimize odors.
- ◆ Keep away from open spark and flame.
- ◆ Do not apply in damp conditions or where mildew is present (remove all traces of mildew).

Optimal Performance Guidelines

- ◆ Always spray in light coats with a sweeping motion to avoid runs.
- ◆ Hold can 8”- 12” from surface.
- ◆ Surface to be painted should be clean, dry and dull, and free from oil, grease and other contaminants.
- ◆ Invert and spray to clear nozzle after use.
- ◆ Follow label directions for application

Technical Information

Gloss Range
≤ 10 (60 ° angle)

Vehicle Type Acrylic Lacquer

Spreading Rate
315 g will cover up to 1.6 square meters or up to 17 square feet per coat, depending on the porosity and texture of the substrate

% Solids (based on Jamaica Orange)

by Volume: 12

by Weight: 16

Weight per 315 g can 0.438 Kg including cap & can

Dry Time

(Based on normal conditions)

To Recoat 10–30 minutes

Surface Temperature

Minimum: 10 °C or 50 °F

Maximum: 32 °C or 90 °F

Storage Temperature

Minimum: 5 °C or 41 °F

Maximum: 35 °C or 95 °F

Flash Point Flammable

Container Sizes

A127-JO –Jamaica Orange	315 g	1740-254
A127-SO –Sunset Orange	315 g	1740-263
A127-HP –Hot Pink	315 g	1740-245
A127-SY –Saturn Yellow	315 g	1740-236
A127-TG –Turf Green	315 g	1740-227

*Contact your local municipal office for specific disposal guidelines in your region.