



MILDEW OFF RTU C17-80

Description

Natura Ready to Use Mildew Off was developed to perform optimally through the combination of proprietary formulation and advancement. This product offers excellent removal of mildew stains for non-metal exterior surfaces.

Recommended Substrates

Wood Surfaces – Non-Metal Surfaces

Tinting and Base Information

N/A

Features

Ready to Use
Mildew Removal
Non-corrosive to skin
Home Owners Guarantee

Benefits

Removes Mildew
Removes organic material
Non-Corrosive, does not contain bleach

Regulatory Conformance and Approvals

N/A

Technical Data

Vehicle Type: xxxxxxxxxxxx

Gloss Range: N/A

Spread Rate: 250-400ft² per gallon depending on age and porosity of surface.

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Spread Rate do not include loss due to surface irregularities, surface porosity, and application method

Volume Solids*: N/A

Weight Solids*: N/A

Drying Time: @ 25°C; 50% Relative Humidity

To Touch – N/A

To Recoat – N/A

To Full Cure – N/A

Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.

Surface Temperature:

Material – 10°C (50°F) to 32° (90°F)

Ambient - 10°C (50°F) to 32° (90°F)

Substrate - 10°C (50°F) to 32° (90°F)

Storage of material at elevated temperatures for prolonged periods may experience skinning.

Viscosity: N/A

Flash Point: N/A

Colour: Clear

Fragrance: Odourless

pH: 5.0

Specific Gravity: 1.01

Disposal: Contact your local environmental regulatory office or your municipality for specific guidelines

Container Sizes:

C17-80 4L 1874R401

General Preparatory Steps and Application Info

-Ready to Use.

-Do not dilute.

-Protect and cover all areas where the Mildew Off will come into contact, such as foliage, metal, and glass.

-Dampen the wood to be cleaned.

-Spray on the solution, keep surface damp with product, and do not allow the product to dry on surface.

-Do not use on metal or metal siding.

-Allow cleaning solution to stand for 5-10 minutes and repeat above.

-Scrub lightly with bristle brush. Do not use a wire brush.

-Rinse the surface thoroughly with a pressure washer (500psi) or garden hose.

-Depending on severity of surface, repeat and rinse again.

-Depending on aggressiveness of cleaning, the wood surface might fir up necessitating a quick sanding. Do not sand smooth.

-Possibly the wood surface is too far gone negating the use of cleaner.

-Do not mix with products containing bleach or ammonia.

-Will not damage or remove paint, stain, or clear finishes off the surface. Try a test spot first to gauge performance.

-Do not apply in direct sun.

-Please take extra precaution near and around the project to protect foliage, metal, and glass.

-Not intended to be used on resin or composite material.

-Follow label directives for application requirement. Consult your local Paint Department.

-Stir thoroughly before and occasionally during use.

-Can be used as maintenance cleaner once or twice a year.

Application Equipment: Apply with a garden sprayer and a bristle brush.

Thinning: N/A