



EXT. SAFE STRIP C17-90

Description

Natura Exterior Safe Strip was developed to perform optimally through the combination of proprietary formulation and advancement. This product is a safe effective way to remove water-based, oil-based, semi and solid stains, and paint from exterior wood surfaces.

Recommended Substrates

Wood Surfaces – Vertical and Horizontal Application

Tinting and Base Information

N/A

Features

Ready to Use
Gel Formula
Non-corrosive
Home Owners Guarantee

Benefits

Safe option compared to methylene chloride
Safe option compared to sodium hydroxide
Clings to vertical surface

Regulatory Conformance and Approvals

N/A

Technical Data

Vehicle Type: N/A

Gloss Range: N/A

Spread Rate: 75-160ft² per gallon depending on age and porosity of surface.

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Spread Rate do not include loss due to surface irregularities, surface porosity, and application method

Volume Solids*: N/A

Weight Solids*: N/A

Drying Time: @ 25°C; 50% Relative Humidity

To Touch – N/A

To Recoat – N/A

To Full Cure – N/A

Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.

Surface Temperature:

Material – 10°C (50°F) to 32° (90°F)

Ambient - 10°C (50°F) to 32° (90°F)

Substrate - 10°C (50°F) to 32° (90°F)

Storage of material at elevated temperatures for prolonged periods may experience skinning.

Viscosity: N/A

Flash Point: N/A

Colour: White

Fragrance: Almond

pH: 11.2

Specific Gravity: 1.02

Disposal: Contact your local environmental regulatory office or your municipality for specific guidelines

Container Sizes:

C17-90 4L 1874R402

General Preparatory Steps and Application Info

-Ready to Use.

-Do not dilute.

-Cover plants and shrubs or wet thoroughly with water.

-Protect and cover any areas that the Safe Strip will come in contact such as foliage, metal, and glass.

-Shake or Stir thoroughly before and occasionally during use.

-Dampen the area to be stripped.

-Brush or roll on a uniform coat of the solution and allow it to stand for 20-30 minutes.

-Do not allow the product to dry on surface. Re-apply if necessary.

-Scrub a small section to gauge whether the existing coating is lifting.

-As the coating begins to lift, use a stiff bristle brush or scraper. Do not use a wire brush.

-Likely a second application is necessary depending on the film of build of existing coating. Repeat the above steps.

-Rinse the surface thoroughly with a pressure washer (500psi) or a garden hose.

-Rinse adjacent surface to effectively remove residual stripper.

-Allow surface to dry until moisture content in wood surface is below 15%.

-Surface might need to be sanded. Do not sand smooth.

-Depending on aggressiveness of cleaning, the wood surface might fir up necessitating a quick sanding. Do not sand smooth.

-Do not mix with other lift products.

-Will not neutralize mold or mildew. Please consult with your local paint department.

-Try a test spot first to gauge performance.

-Do not apply in direct sunlight.

-Not intended to be used on resin or composite material.

-Follow label directives for application requirement. Consult your local Paint Department.

Application Equipment: Apply with brush or roller or garden sprayer.

Thinning: N/A