



# INT. SAFE STRIP C17-90

## Description

Natura Interior Safe Strip was developed to perform optimally through the combination of proprietary formulation and advancement. This product is a safe effective way to remove water-based, oil-based, semi and solid stains, and paint from interior surfaces.

## Recommended Substrates

Wood, Masonry, and Metal surfaces

## Tinting and Base Information

N/A

## Features

Ready to Use  
Gel Formula  
Non-corrosive  
Home Owners Guarantee

## Benefits

Safe option compared to methylene chloride  
Safe option compared to sodium hydroxide  
Clings to vertical surface

## Regulatory Conformance and Approvals

N/A

## Technical Data

**Vehicle Type:** N/A

**Gloss Range:** N/A

**Spread Rate:** 21-43ft<sup>2</sup> per litre depending on age and porosity of surface.

**Wet Film Thickness:** N/A

**Dry Film Thickness:** N/A

*Spread Rate do not include loss due to surface irregularities, surface porosity, and application method*

**Volume Solids\*:** N/A

**Weight Solids\*:** N/A

**Drying Time:** @ 25°C; 50% Relative Humidity

To Touch – N/A

To Recoat – N/A

To Full Cure – N/A

*Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.*

## **Surface Temperature:**

Material – 10°C (50°F) to 32° (90°F)

Ambient - 10°C (50°F) to 32° (90°F)

Substrate - 10°C (50°F) to 32° (90°F)

*Storage of material at elevated temperatures for prolonged periods may experience skinning.*

**Viscosity:** N/A

**Flash Point:** N/A

**Colour:** White

**Fragrance:** Almond

**pH:** 11.2

**Specific Gravity:** 1.02

**Disposal:** Contact your local environmental regulatory office or your municipality for specific guidelines

## **Container Sizes:**

C17-90 1L 1650R350

## **General Preparatory Steps and Application Info**

-Ready to Use.

-Do not dilute.

-Protect and cover any areas that the Safe Strip will come in contact.

-Shake or Stir thoroughly before and occasionally during use.

-Brush, roll, spray on a uniform coat of the solution and allow it to stand for 30-60 minutes.

-Do not allow the product to dry on surface. Re-apply if necessary.

-Scrub a small section to gauge whether the existing coating is lifting.

-As the coating begins to lift, use a stiff bristle brush or scraper. Do not use a wire brush.

-Likely multiple applications are necessary depending on the film of build of existing coating. Repeat the above steps.

-Wipe off with a dampen cloth to remove product residue.

-Surface might need to be sanded. Do not sand smooth.

-Do not mix with other lift products.

-Will not neutralize mold or mildew. Please consult with your local paint department.

-Try a test spot first to gauge performance.

-Do not apply in direct sunlight.

-Not intended to be used on resin or composite material.

-Follow label directives for application requirement. Consult your local Paint Department.

**Application Equipment:** Apply with brush or roller

**Thinning:** N/A