



CEMENT BOND C210-20

Description

HOME CRETE Interior and Exterior Cement Bond is an acrylic additive that enhances the strength and adhesion of cement base products. The admixture provides a tough, durable, flexural, and adhesion for resurfacing cement projects.

Recommended Substrates

Concrete and Masonry Repairs

Tinting and Base Information

N/A

Features

Interior and Exterior
100% Acrylic Formulation
Liquid Admixture
Home Owners Guarantee

Benefits

Improves Adhesion
Improves Flexibility
Improves Strength
Easy soap and water clean-up

Regulatory Conformance and Approvals

N/A

Technical Data

Vehicle Type: 100% Acrylic

Gloss Range: N/A

Spread Rate: N/A

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Spread Rate do not include loss due to surface irregularities, surface porosity, and application method.

Volume Solids*: N/A

Weight Solids*: N/A

*Weight per N/A

Drying Time: @ 25°C; 50% Relative Humidity

To Touch – 20 minutes

To Traffic – 24-48 hours

To Full Cure – N/A

Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.

pH: 9.4

Colour: White

Fragrance: Mild Acrylic

Specific Gravity: 1.02

Surface Temperature:

Material – 10°C (50°F) to 32° (90°F)

Ambient - 10°C (50°F) to 32° (90°F)

Substrate - 10°C (50°F) to 32° (90°F)

Storage of material at elevated temperatures for prolonged periods may experience skinning.

Viscosity: N/A

Flash Point: N/A

Disposal: Contact your local environmental regulatory office or your municipality for specific guidelines

Container Sizes:

C210-20 1L 2010R932 4L 2010R941

General Preparatory Steps and Application Info

- Surface must be clean, sound, loose of all material, and dry
- Remove all loose material, dirt, mildew, glue, grease, stains, and any other surface contamination.
- Remove all standing water.
- Repair all moisture damage and deter all moisture problems.
- Follow label directives for application requirement. Consult your local Paint Department.

Admixture Option #1: Mix 1-part cement bond and 3 parts of water. Brush on the mixture on repair area and quickly place prepared cement mixture. Maximum placement time is 20 minutes. Follow label directives of cement mix.

Admixture Option #2: For maximum performance use straight cement bond to cement mix (instead of water) for strongest bond and highest strengths. Follow label directives of cement mix.

Application Equipment: (Option #1) Apply with a high-quality brush, Brush – Pure Bristle.

Thinning: N/A