



ACRYLIC-MODIFIED DRIVEWAY SEALER C210-10

Description

BlackGold Driveway Sealer is a premium matte finish that protects against gas, oil, salt, and automotive fluids. It provides a penetrating and protective film that will extend driveway life. Formulated for our Canadian Climate.

Recommended Substrates

Asphalt Laneways / Driveways – Residential and light commercial use

Tinting and Base Information

C210-10* Black

*Cannot be tinted.

Features

Exterior
Acrylic-Modified Formulation
2x the coverage
High Performance Soy-based formula.
Durable Finish
Home Owners Guarantee

Benefits

Outstanding protective finish
Easy to maintain and clean
Non-Tracking and fast drying
Excellent wear and durability
Easy soap and water clean-up

Regulatory Conformance and Approvals

N/A

Technical Data

Vehicle Type: Acrylic-Modified (Soy-based) Resin

Gloss Range: <5 (60° angle) based on the C210-10

Spread Rate: Up to 46.5m² or 500ft² per 5L, up to 139m² or 1500ft² per 17L on smooth and non-porous surfaces.

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Spread Rate does not include loss due to surface irregularities, surface porosity, and application method

Volume Solids*: N/A

Weight Solids*: 18.30%

*Weight per N/A

Drying Time: @ 25°C; 50% Relative Humidity

To Recoat – 1 hour

To Touch – 3 hours

To Full Cure – 24-48 hours (light vehicle traffic)

Drying times will vary depending on ambient temperature, humidity, film build, colour, and air movement.

Colour: Super Matte Black

Fragrance: Ammonia

Specific Gravity: 1.07

Surface Temperature:

Material – 10°C (50°F) to 32° (90°F)

Ambient - 10°C (50°F) to 32° (90°F)

Substrate - 10°C (50°F) to 32° (90°F)

Storage of material at elevated temperatures for prolonged periods may experience skinning.

Viscosity: N/A

Flash Point: N/A

Disposal: Contact your local environmental regulatory office or your municipality for specific guidelines

Container Sizes:

C210-10 5L 2060-680 17L 2060-694

General Preparatory Steps and Application Info

- Surface must be cleaned with BlackGold Concrete and Asphalt cleaner, rinsed, and dried.
- Fill cracks with BlackGold Acrylic Crack Filler if applicable.
- Not recommended for municipal, county, provincial roads application.
- Residential and light commercial use.
- Does not contain coal tar pitch.
- Do not apply on new asphalt surface. Age for a minimum of 1 year.
- Lightly dampen the surface to maximize coverage of product and prevent lap marks.
- Apply sealer in a thin coat with the use of split foam roller and paint tray.
- Do not pour directly on the driveway and spread with the roller or squeegee.
- Do not apply over Coal-Tar base products.
- Do not over-apply or apply too thickly as it may seal and damage asphalt surface (spider cracks).
- 2 thin coats are recommended at 24-48 months intervals depending on use. A thin maintenance coat is possible every 12 months.
- Asphalt surface should be in reasonable condition with no exposed aggregate.
- Do not apply in direct sun or if rain is imminent (within 24 hours).
- Follow label directives for application requirement. Consult your local Paint Department.
- Once sealed, coating will be slippery under wet or icy conditions.
- Stir/shake thoroughly before and occasionally during use.
- If using more than one can of the same, intermix to ensure uniform finish.

Application Equipment: Apply with a high-quality nylon brush or a split foam roller.

Thinning: Water - Not necessary but no more than 10%-12% of volume.